



SSQC Straight Connectors



SSQC connectors are manufactured using special grade polyamide material which offers high impact strength. Metal threads offer extremely high connection strength ensuring safety & reliability.

Applications



Industrial Machinery



Solar & Wind Installations

Material : Special Grade Polyamide 6

Colour : Black & Grey

Temp : -40°C to +105°C, Short Term: 150°C

Protection Degree : IP68 (Using Suitable O-ring & Washers)
Free of Halogens, Cadmium, Phosphorous & Sulphur

Metric Thread

Part Number	Thread Size	Length (mm)	Height H (mm)	Dia (D) mm	PPQ (pcs)
SSQC-M12X07	M12 x 1.5	10	34.5	17	100
SSQC-M16X10	M16 x 1.5	10	36	20.2	100
SSQC-M20X17	M20 x 1.5	13	45	29.7	100
SSQC-M25X17	M25 x 1.5	13	45	29.7	100
SSQC-M25X23	M25 x 1.5	13	48	37.4	100
SSQC-M32X23	M32 x 1.5	13	48	37.4	50
SSQC-M32X29	M32 x 1.5	12	51	44	50
SSQC-M40X29	M40 x 1.5	12	51	44	50
SSQC-M40X29	M40 x 1.5	14	54	52	50
SSQC-M50X36	M50 x 1.5	14	54	52	20
SSQC-M50X48	M50 x 1.5	14.5	55	64	20
SSQC-M63X48	M63 x 1.5	14.5	55	64	10

PG Thread

Part Number	Thread Size	Length (mm)	Height H (mm)	Dia (D) mm	PPQ (pcs)
SSQC-P07X07	M12 x 1.5	10	34.5	17	100
SSQC-P09X10	M16 x 1.5	9.5	36	20.2	100
SSQC-P11X12	M20 x 1.5	9.5	38	23.2	100
SSQC-P16X17	M25 x 1.5	13	43.5	29.7	100
SSQC-P21X23	M32 x 1.5	13	48	37.4	50
SSQC-P29X29	M32 x 1.5	12	51	44	50
SSQC-P36X36	M40 x 1.5	14	54	52	50
SSQC-P48X48	M40 x 1.5	14.5	55	64	20

X: G-Grey, B-Black