

SSRG Elbow Connectors Thread



SSRG connectors are manufactured using special grade polyamide material which offers high impact strength. Metal threads offer extremely high connection strength ensuring safety & reliability.

- Material** : Special Grade Polyamide 6
- Colour** : Black & Grey
- Temp** : -40°C to +105°C, Short Term: 150°C
- Protection Degree** : IP68 (Using Suitable O-ring & Washers)

Free of Halogens, Cadmium, Phosphorous & Sulphur

Applications



Industrial Machinery



Solar & Wind Installations

Part Number	Thread Size	Thread Length (mm)	Height H (mm)	Length (mm)	Dia (D) mm	PPQ (pcs)
SSRG-M10X07	M10 x 1.5	10	33.5	32	17	100
SSRG-M12X10	M12 x 1.5	10	36	34	20.2	100
SSRG-M16X12	M16 x 1.5	10	42	47	23.7	100
SSRG-M20X17	M20 x 1.5	13	50	49	29.7	100
SSRG-M25X23	M25 x 1.5	13	57	56.2	37.4	50
SSRG-M32X29	M32 x 1.5	12	67.5	63	44	50
SSRG-M40X36	M40 x 1.5	12	83	70	52	50
SSRG-M50X48	M50 x 1.5	14	88	83	64	50
SSRG-M63X48	M63 x 1.5	14	88	83	64	20

Part Number	Thread Size	Thread Length (mm)	Height H (mm)	Length (mm)	Dia (D) mm	PPQ (pcs)
SSRG-P07X07	PG7	10	33.5	32	17	100
SSRG-P09X10	PG9	10	36	34	20.2	100
SSRG-P11X12	PG11	10	42	37	23.7	100
SSRG-P16X17	PG16	12	50	49	29.7	100
SSRG-P21X23	PG21	12	57	56.2	37.4	50
SSRG-P29X29	PG29	12	67.5	63	44	50
SSRG-P36X36	PG36	12	83	70	52	50
SSRG-P48X48	PG48	14	88	83	64	20